



*The Signature  
for Success*

## Promotional & Marking Product Range

Spec. No. : PM238  
Date of Issue : 26/04/00  
Supersedes : Draft

<b>Product Code</b>	-	DS/2 Polyester
<b>Adhesive Reference</b>	-	RI-AHT/RI-AHT
<b>Description</b>	-	Clear polyester support

### Face Material

Caliper	-	12	microns (+/-10%)
Substance	-	16	gsm (+/-10%)
Shrinkage	-	Nil	
Recommended Life	-	3	years

### Adhesive

Adhesive Type	-	Permanent acrylic
Tack	-	High
Resistance to Sunlight	-	Very good
Minimum Application Temperature	-	+5°C
Service Temperature	-	-30 to +120°C
Cohesive Strength	-	High
Initial Adhesion	-	1300 g/25mm
Adhesion at 48 Hours	-	2000+ g/25mm

### Release Liner

Type of Backing	-	Kraft-Clay ctd ss sil./1 side PE ctd ss sil.
Colour	-	W / W
Substance	-	140 / 72 gsm (+/-10%)
Caliper	-	150 / 80 microns (+/-10%)

**Typical Applications:**      **General mounting applications**

**Available width:**              **1.0m**



*Any values presented in this data sheet are typical. The information is given in good faith but without warranty.*

Ritrama (UK) Limited, Lynwell Road,  
Lyntown Trading Estate, Eccles,  
Manchester M30 9QG, ENGLAND  
Tel: 0161 786 1760  
Fax: 0161 786 1761

Ritrama s.p.a.,  
Via della Guerrina, 108,  
20052 Monza, ITALY  
Tel: (039) 839215  
Telex: 330559 RITRAM I  
Fax: (039) 834718

Ritrama Duramark,  
800 Kasota Avenue SE,  
Minneapolis, MN 55414, U.S.A.  
Tel: (612) 378 2277  
Fax: (612) 378 9327